

# nora dryfix mr

Double-sided dry adhesive tape for the installation of nora floor coverings in high moisture areas—no need for relative humidity testing, in-situ probes or waiting for adhesives to dry. It is easy to install with no mixing or adhesive cleanup and allows for immediate traffic post-installation.



## **Product Construction Specifications**

Product: nora dryfix™ mr, Article 6556

Material Composition: A quick and easy dry adhesive tape used to install specific nora® rubber floor coverings (2 mm – 4 mm) in high moisture areas.

Material Description/Size: 76 cm x 76.2 m (~30 in x 250 ft) dry adhesive tape with a recyclable white release paper in a white cardboard box.

## **Technical Data**

Shelf Life:	24 months
Coverage:	~625 SF per roll
Moisture Limit:	99% RH, no vapor retarder required
Freeze/Thaw stable:	Stable per ASTM D7149 at 0°F (- 18°C)

## **Health + Environmental Specifications**

Indoor Air Quality: GREENGUARD Gold Certified for low VOC emissions in compliance with CDPH 01350.

LEED v4: Contributes to IEQ credits

Material Composition: Free of organic solvents, formaldehyde, asbestos, lindane, rosins, phthalates, or any other volatile components.

VOC Content: In compliance with the SCAQMD Rule 1168 Standard for Rubber Floor Adhesives, which has a VOC limit of 60 grams/liter.

## **Installation**

Site Conditions: The installation area must be fully enclosed, weather tight, and climate controlled between 63°F and 75°F and 40% to 60% ambient relative humidity (RH) for at least 48 hours prior, during and 72 hours after installation.

Substrate Requirements: Concrete, wood, metal, and existing floors (existing floors must be only one layer and non-cushioned back); refer to the nora Installation Instructions for details. Do not install in areas with known hydrostatic moisture, alkali silica reaction or osmotic blistering problems.

Unique Characteristics:

- Excellent for heavy traffic and heavy rolling loads (no forklift traffic)
- Moisture resistance up to 99% relative humidity (RH)
- No RH testing and no vapor retarder required
- Suitable for all common substrates
- Reliable in high performance areas
- No necessary open time required
- Non-flammable and freeze/thaw stable
- Less downtime with immediate trafficking after installation
- If specified, hot or cold welding of flooring can commence immediately (areas that are not climate controlled must be welded)

For complete installation instructions refer to the nora Installation Instructions.

## **Disclaimer**

It is the user's responsibility to read, understand and follow the nora Installation Instructions, Product Data Sheet, and Safety Data Sheet available on [www.nora.com](http://www.nora.com). You should comply with all applicable OSHA, local, state, and federal regulations.

## **Storage**

Room temperature and away from direct sunlight.

## **Post-Installation Traffic**

- All traffic is allowed immediately post-installation.

Contact the nora Technical Department for confirmation of adhesive and flooring limits.

## **Warranty**

Refer to the nora Limited Warranty - Americas.

Current nora Installation Instructions, Guide Specifications, Maintenance Guidelines, and Limited Warranties can be found at [www.nora.com](http://www.nora.com).

nora®, norament®, and noraplan® are trademarks owned by nora systems GmbH and registered in the United States, Canada, and other countries. All other trademarks are the property of their respective owners.

Updated: April 2024